

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PC

A1

(51) International Patent Classification 6:

A61B 5/06, 8/08, A61M 25/01, A61B 17/39

(11) International Publication Number:

WO 96/05/6

(43) International Publication Date:

29 February 1996 (29.19.9)

(21) International Application Number:

PCT/US95/01103

(22) International Filing Date:

24 January 1995 (24.01.95)

(30) Priority Data:

08/293,859

19 August 1994 (19.08.94)

us

(71) Applicant (for all designated States except US): BIOSENSE, INC. [US/US]; 40 Ramland Road South, Orangeburg, NY 10962 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BEN-HAIM, Shlomo [IL/IL]; 101 Yefe Nof Street, 34454 Haifa (IL). OSADCHY, Daniel [IL/IL]; 48A Harofe Street, 34367 Haifa (IL). PELESS, Udi [IL/IL]; P.O. Box 420, 4500 Evan Yehuda (IL). GREENBERG, Ilan [IL/IL]; 15 Geula Street, 33198 Haifa (IL).

(74) Agents: DIPPERT, William, H. et al.; Cowan, Liebowitz & Latman, P.C., 1133 Avenue of the Americas, New York, NY 10036-6799 (US).

(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LT, LU, LV, MD, MG, MN, MW, MX, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ).

Published

With international search report.

(54) Title: MEDICAL DIAGNOSIS, TREATMENT AND IMAGING SYSTEMS

(57) Abstract

A locating system for determining the location and orientation of an invasive medical instrument, for example a catheter (10) or endoscope, relative to a reference frame, comprising: a plurality of field generators (18, 20, 22) which generate known, distinguishable fields, preferably continuous AC magnetic fields, in response to drive signals; a plurality of sensors (30, 32, 34) situated in the invasive medical instrument (10) proximate the distal end thereof which generate sensor signals in response to said fields; and a signal processor (26) which has an input for a plurality of signals corresponding to said drive signals and said sensor signals and which produces the three location coordinates and three orientation coordinates of a point on the invasive medical instrument.

